

RESIN INFORMATION SHEET

Product Name	TOYOPEARL [®] MX-Trp-650M (A multimodal cationic and hydrophobic resin for protein purification)	
Part Numbers	0022817	TOYOPEARL MX-Trp-650M, 25 mL
	0022818	TOYOPEARL MX-Trp-650M, 100 mL
	0022819	TOYOPEARL MX-Trp-650M, 1 L
	0022820	TOYOPEARL MX-Trp-650M, 5 L

Product Description	TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.		
	separates molecules on the basis of ionic and	in is designed for mixed-mode separations. This chromatographic mode d hydrophobic interactions between the sample and the resin. The aqueous solution with a gradient of increasing ionic strength or pH	
Operating	Packing pressure	Typically 0.3 MPa	
Conditions	Shipping solvent	20 % (v/v) ethanol	
	Shipping formulation	72 % (v/v) slurry in shipping solvent (*)	
	Pressure limiting factor	Depend on column hardware (typically 0.7 MPa)	
	Operating linear flowrate	Typically 10 - 600 cm/hour	
	Long-term storage conditions	20 % (v/v) ethanol (in a non-UV light transmitting opaque container)	
	Cleaning-in-place/Sanitization	0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl	
Specifications	Particle size distribution (min. 80 % within range)	50 - 100 μm	
	Ion exchange capacity	0.08 - 0.15 eq/L	
	Protein adsorption capacity (of γ -globulin)	Min. 75 g/L	
	Bacterial count	Max. 100 CFU/mL	
	Endotoxin concentration	Max. 10.0 EU/mL	
	Eluable matter	Max. 0.2 % (for dry gel)	
	Foreign substance (colored particle)	Max. 6	
Additional	Appearance	White resin slurry which settles upon standing	
Information	Mean pore diameter (base resin)	100 nm (*)	
		(*) The value is for reference only, not guaranteed.	

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.